

Panels

The Nylofor 3M-G system is a unique quality fencing system designed specifically for golf and lifestyle estates.

Applications

The Nylofor 3M-G system is highly recommended for professional fencing of golf estate developments; public spaces; lifestyle estates and general purpose sports areas

Nylofor[®] 3M-G

BENEFITS

Extra long lifetime

The wire is galvanised, resistance welded and plastic coated with maximum adhesion. The coating technology of Betafence is state of the art and guarantees extra long lifetime.

Rigidity and quality

The panels are heavy welded mesh with rectangular meshes and horizontal reinforcements which give the panels a high rigidity. Nylofor 3M-G provides high quality with a high aesthetic value.

Rapid and fault-free installation

All components are perfectly harmonised with each other and developed to give a professional quality fence, installed with maximum efficiency.

Complete system

The system consists of panels in various heights, square, Bekafix or Bekafast posts with a specific fixing system, adapted accessories and a wide assortment of innovative swing and sliding gates.

Special

Panels have a V beam section with double wires. Mesh of V: 100mm x 40mm. Apertures just small enough to prevent golf balls from going through.

Unique colour of coating blends in very well with architectural designs.



Panels

The panels have a width of 3000 mm and are available in heights: from 1030; 2030 and 2430 mm. The panels have vertical barbs of 30 mm at one side, the barbs can be placed at the top or at the bottom.

The horizontal reinforcements give the panels extra rigidity.

The meshes are 100 x 40 mm, as well as the reinforcements.

The wire diameter is 4,6 mm.



Posts and fixing

Bekafix Post System

The panels are fixed lateral on the posts with specific fixators made out of polyamide or metal (security). The welded tubular posts (70 x 44 mm), in H-shape are covered with a plastic cap.

Optional can also be chosen for square posts.

See Nylofor 3D.



Bekafast Post System

Lateral fixing of the Nylofor Medium panels on the Bekafast post. Without accessories. Perfect fixing of the reinforcements of the panel in the post profile.

The Bekafast posts (60 x 50 mm) are covered with a plastic cap.



Square post system

The panels are fixed on the front side of the posts by means of fixators and security bolts. The welded square tubular posts (60 x 60 x 1,50 mm) have inserts for fixing the panels with the fixators and are covered with a plastic cap.

Gates

The Nylofor Medium system is totally finished and safely equipped with high tech gates type Nylofor or Robusta: single and double gates, swing and sliding gates.

Coating techniques

Panels made out of galvanised wires. A pre-treatment process guarantees a perfect PVC-coating adhesion to the product surface.

The posts are in- and outside galvanised (min. coating 275g/m², both sides together), in accordance with Euro norm 10326. Afterwards an adhesion coating is applied and finally the posts are plastic coated (min. 60 micron).

Colours

Standard colours: green RAL 6005 or black grey RAL 7021.

Other colours on request

ASSORTMENT NYLOFOR 3M-G

Fence height mm	Panels width x height mm	Number of reinforcements per panel	Post length mm	Bekafix posts		Bekafast posts	Square posts	
				Number of fixings per intermediate & corner post	Number of fixings per end post		Number of fixings per intermediate & end post	Number of fixings per corner post
1030	3000 x 1030	2	1500	4	2	No Accessories	3	6
2030	3000 x 2030	4	2600	8	4	No Accessories	6	12
2430	3000 x 2430	4	3200	8	4	No Accessories	7	14



Physical Address:

Berg River Business Park
Cnr Jan van Riebeeck Drive &
Borssenberg Road
Dal Josafat, Paarl, 7646

Postal Address:

P O Box 159, Blackheath, Cape Town, 7581

Phone: +27 (0)861 BFENCE
Email: info@betafence.co.za
Website: www.betafence.co.za